




FERTILIZER & LIME SPREADERS

- Accurate spread pattern.
- Hydraulic control spinners and multiple drop point adjustment ensuring accurate spreading.
- Hydraulic drive machines are VRT ready (Variable Rate Technology) and compatible with most GPS systems.
- Simple and easy to operate ground drive or hydraulic drive machines.
- Alpler load cells ensure accurate spreading.
- Ability to customise machine to customer requirements.
- Stainless spreading deck and stainless wearing parts were required. All nuts/bolts were required are stainless steel.
- A commitment to develop products to customer requirements and beyond.





ISOBUS Rate Controller



Computer Control



Twin Chain Option



Fertilizer Disks up to 36 m



Lime, Manure and Gypsum



Flotation Tyres



Eaton Motors



Window

MODEL		GSR 3	GSR 4	GSR 4L	GSR 5	GSR 5L	GSR 6	GSR 8	GSR 10	GSR 11C	GSR 11	GSR 13	GSR 15	GSR 20
General Specifications	CU. Capacity	2,5	3,5	3,2	4,6	4,0	4,8	6,0	7,9	9,0	9,0	10,8	12,7	16,0
	Tonage Fertiliser	3	4,5	4	5,5	5	5,76	7,25	9,5	11	11	12,5	15	20
	Tonage Lime	3,5	5	4,5	6,4	5,6	6,72	8,4	11	12,5	12,5	15	18	22,5
	Bin Length	2000	2000	2400	2400	3000	2400	3000	3000	3000	3000	4000	4000	6000
	Bim Width	1800	1800	1800	1800	1800	2290	2290	2290	2290	2290	2290	2290	2290
	Bin Height	1068	1400	954	1288	1288	1315	1315	1654	1747	1747	1654	1747	1654
	Conveyor Drive	Ground Wh.	Ground Wh.	Ground Wh.	Ground Wh.	Ground Wh.	Ground Wh.	Ground Wh.	Computer	Computer	Ground Wh.	Section Con	Section Con	Section Con
	Tyres	11.5/80x15.3	400/60x15.5	14.9x24	14.9x24	14.9x24	16.5/85x24	16.5/85x24	23.1x26	23.1x26	23.1x26	650/75Rx32		
	Single or Tandam	Single	Single	Single	Single	Single	Single	Single	Single	Single	Single	Variable	Variable	Tandam
	Hyd Brakes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
	Removable Drawbar	Yes	Yes	Yes	Yes	No	No	No	No	Yes	Yes	Yes	Yes	Yes
	Sprung Drawbar	No	No	No	No	No	No	No	No	Yes	Yes	Yes	Yes	Yes
	Adjustable DB height	No	No	No	Single	Single	Single	Single	Single	Single	Single	Single	Single	Single
	Ground Drive 3 Speed	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes			
	Tachometer	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes		Yes			
	Floor Feed Width	730	730	730	730	730	730	730	730	730	730	730	730	730
	Wheel Option	400/60x15.3	11x22.5	11x22.5	11x22.5	11x22.5	11x22.5	23.1x26	23.1x26	23.1x26	23.1x26	650/65x30.5		
	Axle Track	1700	1700	1700	1700	1800	1800	1800	2000	2000	2000	2200x3000	2200x3000	2200
	Square	70mm	70mm	70mm	70mm	60mm	70mm	70mm	90mm	90mm	90mm			
	Stubs	6	6	6	6	6	8	8	8	8	8	10	10	
Options	Load Cells	X	X	X	X	X	X	X	X	✓	X	✓	✓	✓
	Computer ISO	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	Display	X	X	X	X	X	X	X	✓	✓	X	✓	✓	✓
	Ground Drive 3 Speed	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	X	X	X
	Computer (Hydrolic Drv)	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	Twin Chain Section Control	X	X	✓	✓	✓	✓	✓	✓	✓	✓	✓	X	X
	Roll Tarp.	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	Independent Hyd. Kit	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	Tandem	X	X	X	X	X	X	X	X	X	X	✓	✓	✓
	Production Material	Mild Steel	Mild Steel	Mild Steel	Mild Steel	Mild Steel	Mild Steel	Mild Steel	Mild Steel	Mild Steel	Mild Steel	Mild Steel	Mild Steel	Mild Steel
	Production Material	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel



Adjustable door



Sprung Drawbar



Land Drive Option




STOP Led Lights

L: Long C: Computer



Designed by Transpread Co. (Mr. David Hoyle)



ALMEKS

ALMEKS IMPORT & EXPORT Co.

Kıbrıs Şehitleri Caddesi No: 98/11 Alsancak - İZMİR / TÜRKİYE

+90(232) 463 7044

+90(232) 463 9433

almeks.com.tr

info@almeks.com.tr

/almeks

YouTube /almeks

Download on the App Store

Google play